


3325HC PET Film Double-Sided Tape

 Product Description 			
	3325HC is a clear double side self-adhesive tape consisting of a thin PET carrier and modified acrylic adhesive.		
 Key Features 			
	High bonding strength.		
	Very good adhesion to most common smooth substrate.		
	Good performance in temperature and chemical resistance.		
	Godd handling performance in converting processes.		
 Application Ideas 			
	Used for variety substrate bonding, such as metal panel, plastic and films.		
	Ideal for graphic overlays, nameplates, appliques and decorative trim.		
	Good for mobile phone parts attachment, such as gasket, mesh, insulation films		
	Good for LCD BLU mounting		
	Good for battery pack mounting		
Construction			



♦ Technical Data

Test Item		Unit	Value	Test Method
Thickness of PET film		mm	0.25	GB/T 7125
Initial Adhesion		Ball No.	>5#	GB/T4852,Ball tack. J.dow method at room temperature. Tape size: 100mm*150mm.
180°Peel Adhesion	30min	• N/25mm	>25	GB/T2792,180°peel strength to substrate at room temperature,tape size:25mm*150mm,30 min
	72hrs		>30	
Temperature Range		°C	, -10-90	
Holding Power		hrs	>72	GB/7754,Tensile strength, tape size:25mm*25mm, loading: 1kg
Color		transparent		

♦ Envirument Resistance

Temperature Range Weather Resistance -10°C~90°C Excellent

Shelf Life & Storage Conditions

• Tape in roll form: Shelf life 6 months from the date of manufacture whe stored in original cartons at 20°C and 50% relative humidity.

• Ideal tape application temperature range is 21 °C to 38 °C.

Notes

The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and datas should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng asdhesive tape for each application.

Servtek Materials Technology (Guangzhou) Co.,Ltd



Http: www.servtek.cn Tel : (+86)20-38892652/38255282

Fax: (+86)20-38892205