

2316L

Cotton Paper Tape 棉纸胶带

◆ Technical Data 技术数据

● Product Description

产品说明

2316L is a cotton paper carrier tape with acrylic adhesive double coated . It has a very high level of initial tack and good adhesion to a wide variety of surfaces.

2316L以棉纸为基材，双面涂布亚克力粘合剂，具有非常高的初始粘性，对众多表面都具有良好的粘接性。

● Key Features

主要特点

Excellent initial adhesion. 优异的初粘性。

Excellent resistance to high temperature. 优异的耐高温性。

Good adhesion to film and plastic materials 对塑料材质薄膜具有良好的粘性

● Application Ideas


应用领域

Adhesive to mark, film, power switch, foam materials, fabric materials as well as plastic materials.

粘合各类标识，薄膜，电源开关，发泡材料，织物材料等各类塑料材料。

● Construction

结构



- Acrylic Adhesive 亚克力胶层
- Cotton Paper 棉纸
- Acrylic Adhesive 亚克力胶层
- Paper Release Liner 离型纸

◆ Technical Data 性能指标

Test Item 测试项目	Unit 单位	Value 测试值	Test Method 测试方法
Thickness 厚度	mm	0.16±0.02	ASTM-1000
Initial Adhesion 滚球初粘	Ball No.	> 12#	Ball tack. J.dow method at room temperature. Tape size:100mm*150mm
180° Peel Adhesion 180°剥离力	gf/25mm	2500	ASTM D-3330
Holding Power 保持力	hrs	> 72	ASTM D-3654
Temperature Resistance 耐温性	—	-20℃~120℃	—
Color 颜色	White 白色		—
Release Liner 离型纸	Paper Liner 离型膜		—

◆ Application Guidelines 应用指南

● For maximum bonding result, the application surfaces should be cleaned with a 50:50 mixture (isopropyl alcohol and water). Ideal tape application temperature is ranged from 18℃ to 38℃ and an excellent bond is allowed to dwell 72 hrs.

为了获得最理想的粘合结果，粘合表面应使用异丙醇和水50:50混合物进行清洗。理想的胶带应用温度为21℃~38℃，72小时后可达到最佳粘合效果。

◆ Shelf Life & Storage Conditions 保质期与贮藏条件

●Tape in roll form: Shelf life 12 months from the date of manufacture when stored in original cartons at 20°C and 50% relative humidity.成卷胶带：在20°C和50%相对湿度条件下存放在原来的纸箱，保质期自生产日期起12个月。

◆ Notes 注释

The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and data should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng adhesive tape for each application. 本文件中所包含的产品信息旨在协助您使用仁诚化学产品、并在设计与应用时提供参考。该技术信息和数据只应考虑具有代表性或典型性，并非为产品所作的任何明示或暗示的保证，包括但不限于任何适销性或针对特定用途的适用性。本技术文件所展示的数据结论是针对特定用途的使用者，用户应自行确定仁诚化学产品的适用性。

Servtek Materials Technology (Guangzhou) Co., Ltd



Http: www.servtek.cn

Tel : (+86)20-38892652/38255282

Fax: (+86)20-38892205